

GRM1555C1H5R6DZ01#

" # " indicates a package specification code.



To be discontinued

Reflow OK

Complies with RoHS

< List of part numbers with package codes >
GRM1555C1H5R6DZ01D , GRM1555C1H5R6DZ01W , GRM1555C1H5R6DZ01J

Shape

			
L size		1.0 ± 0.05mm	
W size		0.5 ± 0.05mm	
T size		0.5 ± 0.05mm	
External terminal width e		0.15 to 0.35mm	
Distance between external terminals g		0.3mm min.	
Size code in mm(inch)		1005 (0402)	
Specifications			
Capacitance		5.6pF ± 0.5pF	
Rated voltage		50Vdc	
Temperature characteristics (complied standard)		COG(EIA)	
Temperature coefficient		0 ± 30ppm/	
Temperature range of temperature characteristics		25 to 125	
Operating temperature range		-55 to 125	

Notes
Please use replacements or Recommended.

References

Packaging		Specifications	Minimum quantity
D	180mm Paper taping		10000
J	330mm Paper taping		50000
W	180mm Paper taping (W8P1*)		20000
		* Width : 8mm, Pocket pitch : 1mm	

		Mass (typ.)
1 piece		1.6mg
180mm Reel		118g

⚠ Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it ' s specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.