

GRM1555C1H681JA01#


"#" indicates a package specification code.

Recommended Reflow OK Complies with RoHS

< List of part numbers with package codes >

GRM1555C1H681JA01D , GRM1555C1H681JA01W , GRM1555C1H681JA01J

Shape





118g

1.0 ±0.05mm
0.5 ±0.05mm
0.5 ± 0.05mm
0.15 to 0.35mm
0.3mm min.
1005 (0402)
680pF ± 5%
50Vdc
COG(EIA)
0 ± 30ppm/
25 to 125
-55 to 125

References

Pa	ickaging S	Specifications	Minimum quantity
D	180mm Paper taping	1000	0
J	330mm Paper taping	5000	0
W	180mm Paper taping (W8P1*) * Width : 8mm, Pocket pitch : 1mm	2000	0
		Mass (typ.)	
1 piece		1.6mg	

180mm Reel

1 of 2

🔔 Attention


1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.


Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

Chart of characteristic data (The charts below may show another part number which shares its characteristics.)


Frequency characteristics (ESR, Impedance)




AC voltage characteristics



This PDF data has only typical specifications because there is no space for detailed specifications. Therefore, please reviewour product specifications or consult the approval sheet for product specifications before ordering. S parameter (Smith chart S11)



Capacitance - temperature characteristics





Last updated: 2013/10/23