

# GRM1557U1H9R9CZ01#

"#" indicates a package specification code.


References

#### Reflow OF To be discontinued omplies with RoHS

< List of part numbers with package codes >

GRM1557U1H9R9CZ01D , GRM1557U1H9R9CZ01W , GRM1557U1H9R9CZ01J

## Shape



### Minimum quantity Packaging Specifications D 180mm Paper taping 10000 50000 J 330mm Paper taping

W	180mm Paper taping (W8P1*) * Width : 8mm, Pocket pitch : 1mm	20000

Mass (typ.)	
1 piece	1.6mg
180mm Reel	118g

## Specifications

Size code in inch(mm)

Capacitance	9.9pF ±0.25pF
Rated voltage	50Vdc
Temperature characteristics (complied standard)	U2J(EIA)
Temperature coefficient	-750 ± 120ppm/
Temperature range of temperature characteristics	25 to 85
Operating temperature range	-55 to 125

## Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

0402 (1005)



URL : http://www.murata.co.jp/

Last updated: 2013/11/17