

# GRM155R60J184KE01#

"#" indicates a package specification code.


References

### Available Complies with RoHS

< List of part numbers with package codes >

GRM155R60J184KE01D , GRM155R60J184KE01W , GRM155R60J184KE01J

## Shape



#### Minimum quantity Packaging D 180mm Paper taping 10000 330mm Paper taping 50000 J 180mm Paper taping (W8P1\*) W 20000 \* Width : 8mm, Pocket pitch : 1mm

Specifications

| Mass (typ.) |       |
|-------------|-------|
| 1 piece     | 1.6mg |
| 180mm Reel  | 118g  |

## Specifications

| Capacitance                                      | $0.18\mu F \pm 10\%$ |
|--|----------------------|
| Rated voltage                                    | 6.3Vdc               |
| Temperature characteristics (complied standard)  | X5R(EIA)             |
| Capacitance change rate                          | ± 15.0%              |
| Temperature range of temperature characteristics | -55 to 85            |
| Operating temperature range                      | -55 to 85            |

## 🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL : http://www.murata.co.jp/

Last updated: 2013/11/18