GRM1885C2A150JA01#

"#" indicates a package specification code.










< List of part numbers with package codes > GRM1885C2A150JA01D , GRM1885C2A150JA01J

Shape





-55 to 125

L size 1.6 ± 0.1 mm W size 0.8 ± 0.1 mm 0.8 ± 0.1 mm T size External terminal width e 0.2 to 0.5mm Distance between external terminals g 0.5mm min. Size code in mm(inch) 1608 (0603)

Specifications

Capacitance $15pF \pm 5\%$ 100Vdc Rated voltage COG(EIA) Temperature characteristics (complied standard) Temperature coefficient 0 ± 30ppm/ Temperature range of temperature characteristics 25 to 125

References

Operating temperature range

Packaging		Specifications		Minimum quantity
D	180mm Paper taping		4000	
J	330mm Paper taping		10000	
		Mass (typ.)		
1 piece			6.3mg	
180mm Reel			144g	

1 of 2



- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




muRata Murata Manufacturing Co., Ltd.

URL: http://www.murata.co.jp/


Last updated: 2013/10/20

Chart of characteristic data (The charts below may show another part number which shares its characteristics.)

Frequency characteristics (ESR, Impedance)




AC voltage characteristics




This PDF data has only typical specifications because there is no space for detailed specifications.

Therefore, please reviewour product specifications or consult the approval sheet for product specifications before ordering.

S parameter (Smith chart S11)



Capacitance - temperature characteristics



2 of 2



Last updated: 2013/10/20