


GRM188F51C474ZA01#

Available Flow OK Reflow OK With RoHS

< List of part numbers with package codes > GRM188F51C474ZA01D , GRM188F51C474ZA01J

Shape





"#" indicates a package specification code.

L size		1.6 ± 0.1mm			
W size T size External terminal width e		0.8 ± 0.1mm 0.8 ± 0.1mm 0.2 to 0.5mm			
			Distance between external terminals g		0.5mm min.
			Size code in mm(inch)		1608 (0603)
Specifications					
Capacitance		0.47µF +80/-20%			
Rated voltage		16Vdc			
Temperature characteristics (complied standard)		Y5V(EIA)			
Capacitance change rate		+22.0/-82.0%			
Temperature range of temperature characteristics		-30 to 85			
Operating temperature range		-30 to 85			
References					
Packaging	Specifications	Minimum			

PackagingSpecificationsMinimum quantityD180mm Paper taping4000J330mm Paper taping10000Mass (typ.)1 piece6.3mg180mm Reel144g

1 of 1

🔔 Attention

This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

muRata Murata Manufacturing Co., Ltd.

URL : http://www.murata.co.jp/

Last updated: 2013/10/20