


GRM188R71H681KA01#

"#" indicates a package specification code.



< List of part numbers with package codes > GRM188R71H681KA01D , GRM188R71H681KA01J

Shape





| 1.6 ± 0.1mm 0.8 ± 0.1mm 0.2 to 0.5mm 0.5mm min. 1608 (0603) | |
|---|-------------|
| 0.8 ± 0.1mm 0.2 to 0.5mm 0.5mm min. 1608 (0603) | |
| 0.2 to 0.5mm 0.5mm min. 1608 (0603) | |
| 0.5mm min. 1608 (0603) | |
| 608 (0603) | |
| | |
| | |
| | |
| 680pF ±10% | |
| 50Vdc | |
| X7R(EIA) | |
| ± 15.0% | |
| -55 to 125 | |
| -55 to 125 | |
| | |
| Minim | um quantity |
| | -55 to 125 |

D 180mm Paper taping 4000 J 330mm Paper taping 10000 Mass (typ.) 1 piece 6.3mg 180mm Reel 6.4 144g

1 of 2

🔔 Attention

This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.


muRata Murata Manufacturing Co., Ltd.

URL : http://www.murata.co.jp/


Last updated: 2013/10/20

Chart of characteristic data (The charts below may show another part number which shares its characteristics.)


Frequency characteristics (ESR, Impedance)




DC bias characteristics




Capacitance - temperature characteristics



S parameter (Smith chart S11)



AC voltage characteristics



2 of 2

This PDF data has only typical specifications because there is no space for detailed specifications. Therefore, please reviewour product specifications or consult the approval sheet for product specifications before ordering. muRata Murata Manufacturing Co., Ltd.

Last updated: 2013/10/20