

GRM2165C1H132JA01#

“ # ” indicates a package specification code.

Available


Flow OK

Reflow OK

Complies with RoHS

< List of part numbers with package codes >
GRM2165C1H132JA01D , GRM2165C1H132JA01J

Shape

		
L size	2.0 ±0.1mm	
W size	1.25 ±0.1mm	
T size	0.6 ±0.1mm	
External terminal width e	0.2 to 0.7mm	
Distance between external terminals g	0.7mm min.	
Size code in mm(inch)	2012 (0805)	

Specifications

Capacitance	1300pF ±5%
Rated voltage	50Vdc
Temperature characteristics (complied standard)	COG(EIA)
Temperature coefficient	0±30ppm/°C
Temperature range of temperature characteristics	25 to 125°C
Operating temperature range	-55 to 125°C

References

Packaging		Specifications	Minimum quantity
D	φ 180mm Paper taping		4000
J	φ 330mm Paper taping		10000
		Mass (typ.)	
1 piece			6.4mg
φ 180mm Reel			126g

 Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it ’ s specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2.This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.