


# GRM2165C2A121JA01#

Recommended Flow OK Reflow OK with RoHS

< List of part numbers with package codes > GRM2165C2A121JA01D , GRM2165C2A121JA01J

Shape





"#" indicates a package specification code.

L size	2.0 ± 0.1mm
W size	1.25 ± 0.1mm
T size	0.6 ± 0.1mm
External terminal width e	0.2 to 0.7mm
Distance between external terminals g	0.7mm min.
Size code in mm(inch)	2012 (0805)
Specifications	
Capacitance	120pF ±5%
	100Vdc
Rated voltage	100Vdc C0G(EIA)
Rated voltage Temperature characteristics (complied standard)	
Rated voltage Temperature characteristics (complied standard) Temperature coefficient Temperature range of temperature characteristics	COG(EIA)

PackagingSpecificationsMinimum quantityD180mm Paper taping4000J330mm Paper taping10000

1 of 2

## 🔔 Attention

This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.


# muRata Murata Manufacturing Co., Ltd.

URL : http://www.murata.co.jp/


Last updated: 2013/10/20

### Chart of characteristic data (The charts below may show another part number which shares its characteristics.)


#### Frequency characteristics (ESR, Impedance)




AC voltage characteristics



This PDF data has only typical specifications because there is no space for detailed specifications. Therefore, please reviewour product specifications or consult the approval sheet for product specifications before ordering. S parameter (Smith chart S11)



Capacitance - temperature characteristics





Last updated: 2013/10/20