


GRM2165C2A241JA01#

Available Flow OK Reflow OK with RoHS

< List of part numbers with package codes > GRM2165C2A241JA01D , GRM2165C2A241JA01J

Shape





"#" indicates a package specification code.

L size		2.0 ± 0.1mm	
W size		1.25 ±0.1mm	
T size		0.6 ±0.1mm	
External terminal width e		0.2 to 0.7mm	
Distance between external terminals g		0.7mm min.	
Size code in mm(inch)		2012 (0805)	
Specifications			
Capacitance			240pF ± 5%
Rated voltage			100Vdc
Temperature characteristics (complied standa	rd)		COG(EIA)
Temperature coefficient			0 ± 30ppm/
Temperature range of temperature characteri	stics		25 to 125
Operating temperature range			-55 to 125
References			
Packaging	Specifications		Minimum quantity

D 180mm Paper taping 4000 J 330mm Paper taping 10000 Mass (typ.) 1 piece 6.4mg 180mm Reel 6.4mg

1 of 1

🔔 Attention

This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

muRata Murata Manufacturing Co., Ltd.

URL : http://www.murata.co.jp/

Last updated: 2013/10/20