


GRM216F51H333ZA01#

Available Flow OK Reflow OK with RoHS

< List of part numbers with package codes > GRM216F51H333ZA01D , GRM216F51H333ZA01J

Shape





"#" indicates a package specification code.

L size		2.0 ± 0.1mm
W size		1.25 ±0.1mm
T size		0.6 ± 0.1mm
External terminal width e		0.2 to 0.7mm
Distance between external terminals g		0.7mm min.
Size code in mm(inch)		2012 (0805)
Specifications		
Capacitance		33000pF +80/-20%
Rated voltage		50Vdc
Temperature characteristics (complied standard)		Y5V(EIA)
Capacitance change rate		+22.0/-82.0%
Temperature range of temperature characteristics		-30 to 85
Operating temperature range		-30 to 85
References		
Packaging	Specifications	Minimum quantity

 D
 180mm Paper taping
 4000

 J
 330mm Paper taping
 10000

 Mass (typ.)

 1 piece
 9.6mg

 180mm Reel
 142g

1 of 1

🔔 Attention

This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
 This datasheet has only typical specifications because there is no space for detailed specifications.
 Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

muRata Murata Manufacturing Co., Ltd.

URL : http://www.murata.co.jp/

Last updated: 2013/10/20