


GRM2195C2A102JA01#

Available Flow OK Reflow OK with RoHS

< List of part numbers with package codes > GRM2195C2A102JA01D , GRM2195C2A102JA01J

Shape





"#" indicates a package specification code.

L	_ size			2.0 ± 0.1mm	
V	N size			1.25 ±0.1mm	
Т	size			0.85 ±0.1mm	
E	external terminal width e			0.2 to 0.7mm	
D	Distance between external ter	rminals g		0.7mm min.	
S	Size code in mm(inch)			2012 (0805)	
S	pecifications				
С	Capacitance				1000pF ±5%
R	Rated voltage				100Vdc
Т	emperature characteristics ((complied standard)			COG(EIA)
Т	emperature coefficient				0 ± 30ppm/
Т	emperature range of temper	rature characteristics			25 to 125
C	Operating temperature range				-55 to 125
R	References				
	Packaging		Specifications		Minimum quantity
Γ)	180mm Paper taping		4000	
J		330mm Paper taping		10000)

1 piece 180mm Reel

1 of 1

🔔 Attention

This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

Mass (typ.)

9.5mg

152g

muRata Murata Manufacturing Co., Ltd.

URL : http://www.murata.co.jp/

Last updated: 2013/10/20