


## GRM219R71E274KA01#

Available Flow OK Reflow OK with RoHS

< List of part numbers with package codes > GRM219R71E274KA01D , GRM219R71E274KA01J

Shape





11mg

162g

"#" indicates a package specification code.

L size			2.0 ± 0.1mm	
W size			1.25 ±0.1mm	
T size			0.85 ±0.1mm	
External terminal width e			0.2 to 0.7mm	
Distance between external terminals g			0.7mm min.	
Size code in mm(inch) 20			2012 (0805)	
Specifications				
Capacitance				0.27µF ±10%
Rated voltage				25Vdc
Temperature characteristics (complied standard)				X7R(EIA)
Capacitance change rate				± 15.0%
Temperature range of temperature characteristics				-55 to 125
Operating temperature range				-55 to 125
References				
Packagin	g	Specifications		Minimum quantity
D	180mm Paper taping		4000	
J	330mm Paper taping		10000	

Mass (typ.)

1 piece 180mm Reel

1 of 1

## 🔔 Attention

This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

muRata Murata Manufacturing Co., Ltd.

URL : http://www.murata.co.jp/

Last updated: 2013/10/20