


## GRM21BR61C106KE15#

Complies with RoHS Reflow OF Recommended

< List of part numbers with package codes >  $\mathsf{GRM21BR61C106KE15L}\ ,\ \mathsf{GRM21BR61C106KE15K}$ 

## Shape



L size	2.0 ±0.1mm
W size	1.25 ±0.1mm
T size	1.25 ±0.1mm
External terminal width e	0.2 to 0.7mm
Distance between external terminals g	0.7mm min.
Size code in inch(mm)	0805 (2012)

## Specifications

Capacitance	$10\mu F \pm 10\%$
Rated voltage	16Vdc
Temperature characteristics (complied standard)	X5R(EIA)
Capacitance change rate	± 15.0%
Temperature range of temperature characteristics	-55 to 85
Operating temperature range	-55 to 85

Reference	S
Packaging	Spi

"#" indicates a package specification code.

Packaging	Specifications	Minimum quantity	
L	180mm Embossed taping	3000	
K	330mm Embossed taping	10000	

Mass (typ.)	
1 piece	17mg
180mm Reel	102g

1 of 2

## 🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.


Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




URL : http://www.murata.co.jp/

Last updated: 2013/11/27







DC bias characteristics




Capacitance - temperature characteristics








AC voltage characteristics



Calorific property by ripple current



2 of 2

This PDF data has only typical specifications because there is no space for detailed specifications.

Therefore, please reviewour product specifications or consult the approval sheet for product specifications before ordering.

