GRM31CR71C335KA01#

"#" indicates a package specification code.










< List of part numbers with package codes > GRM31CR71C335KA01L , GRM31CR71C335KA01K

Shape





L size 3.2 ± 0.2 mm W size 1.6 ± 0.2 mm 1.6 ± 0.2 mm T size External terminal width e 0.3 to 0.8mm 1.5mm min. Distance between external terminals g Size code in mm(inch) 3216 (1206)

Specifications

Capacitance $3.3\mu F \pm 10\%$ 16Vdc Rated voltage X7R(EIA) Temperature characteristics (complied standard) Capacitance change rate ± 15.0% Temperature range of temperature characteristics -55 to 125 Operating temperature range -55 to 125

References

Packaging		Specifications		Minimum quantity
L	180mm Embossed taping		2000	
K	330mm Embossed taping		6000	
		Mass (typ.)		
1 piece			52mg	
180mm Reel			144g	

1 of 1

🔔 Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



muRata Murata Manufacturing Co., Ltd.

URL: http://www.murata.co.jp/

Last updated: 2013/10/23