

Tripp Lite 1111 West 35th Street Chicago, IL 60609 USA Telephone: +(773) 869 1234 E-mail: saleshelp@tripplite.com

Model #: INTERNET550U

Internet Office 550VA Ultra-compact Standby 120V UPS with USB port



Highlights

- 550VA ultra-compact 120V standby UPS
- Maintains AC output during power failures
- 4 UPS battery supported outlets, 4 surge-only outlets
- USB port, TEL/DSL protection, Wall mountable, 99% efficient
- NEMA 5-15P input plug and 8 NEMA 5-15R outlets
- This product is ENERGY STAR qualified for its ability to save customers money while helping to protect the environment

Description

Tripp Lite's INTERNET550U standby UPS offers complete protection for PCs, workstations and other sensitive electronics in an attractive ultra-compact, mountable housing. Prevents data loss and system downtime by providing battery supported AC output during brownouts and blackout conditions. 8 output receptacles, two of which are widely-spaced to accommodate large transformer plugs without blocking outlets. 4 outlets with full battery support and surge suppression protect computers, monitors and other vital system components from loss of power. 4 additional outlets with surge suppression-only are ideal for printers and other accessories not requiring battery support. Single line telephone suppression jacks protect modem, fax machine, cordless phone or other peripherals with a standard dialup or DSL phone line connection. USB port with PowerAlert monitoring software (available via web download) and cabling enables safe unattended system shutdown in the case of extended power failure. HID-compliant USB interface enables integration with built-in power management and auto-shutdown features of Windows and Mac OS X. Audible alarm and front panel LEDs offer status information regarding line and battery power operation. 550VA/300 watt power handling ability supports entry-level PCs for up to 17 minutes during power failures. \$100,000 connected equipment insurance (USA, Puerto Rico and Canada only).

Package Includes

- INTERNET550U UPS System
- USB cable
- Instruction manual

Features

- INTERNET550U standby UPS offers complete protection from blackouts, brownouts and surges on both AC and Tel/DSL line connections
- 8 outlets, two of which are widely spaced to accommodate large transformer plugs without blocking outlets
- 4 battery supported outlets protect computer, monitor and vital system peripherals, plus 4 additional surge suppression-only outlets for printers and other system accessories not requiring battery support
- Provides battery derived AC output during blackouts and brownouts
- 550VA/300 watt power handling ability supports a variety of PCs, workstations and other sensitive electronics
- Supports entry-level PC systems up to 17 minutes during blackout conditions
- Built-in single line Tel/DSL line surge suppression protects modem, fax machine or cordless phone
- USB port, PowerAlert software (available via web download) and cabling offer safe unattended shutdown without data loss during extended outages
- HID-compliant USB interface enables integration with built-in power management and auto-shutdown features of Windows and Mac OS X.

- Supports Tripp Lite's Watchdog system service to restore operation to locked equipment through soft reboot of application/OS or hard power off/on reboot of connected equipment ideal for unattended kiosk applications
- Space saving, ultra-compact housing fits almost anywhere
- Keyhole mounting flanges enable secure wallmount installation

Specifications

Output Volt Amp Capacity (VA) 550 Output Vatt Capacity 300 Nominal Output Voltage(s) 115V; 120V Frequency compatibility 60 Hz Output voltage regulation (Battery mode) 115V (+/- 5%) Built-In UPS output 85-15R outlet(s) Surge suppression only output AC waveform (battery mode) 4 UPS outlets, 4 surge-only outlets Output AC waveform (AC battery mode) Sine wave Output AC waveform (AC battery mode) Sine wave Rated input current (at maximu load) 10A Nominal Input Voltage(s) 120V AC UPS Input connection type 5-15P Input circuit breaker 10A UPS Input contellength (h) 6 UPS Input contellength (h) 6 UPS Input cord length (h) 1.8 Recommended Electrical Barrier 15A 120V Electrical Induct runtime (minutes) 3.5 min. (300w) Half load runtime 3.5 min. (300w) Half load runtime 1.2 LEDS indicate power failure and overload status LEDS LAIGEAKS & SWICHES 1.2 LEDS indicate power failure and overload status	OUTPUT	
(waits) 115V: 120V Prequency compatibility 60 Hz Output voltage regulation 115V (+/- 5%) Battery mode) 8 5-15R outlet(s) Surge suppression only 4 UPS outlets, 4 surge-only outlets Output AC waveform (AC mode) Sine wave Output AC waveform (AC mode) Sine wave Nominal Input Voltage(s) 20V AC Supported 10A Nominal Input Voltage(s) 120V AC Supported 10A UPS Input connection type 5-15P Input circuit breaker 10A UPS Input conlection type 5-15P Input circuit breaker 10A UPS Input conlection type 5-15P Input circuit breaker 10A UPS Input conlection type 5-15P Input circuit breaker 10A UPS Input conlection type 5-15P Input circuit breaker 10A UPS Input corl length (ft.) 6 UPS Input corl length (ft.) 6 UPS Input corl length (ft.) 10 minutes (150w) Hali		550
Supported 60 Hz Prequency compatibility 60 Hz Output voltage regulation 115V (+/.5%) Battery mode) 8 5-15R outlet(s) Surge suppression only outlets 4 UPS outlets, 4 surge-only outlets Output AC waveform (AC mode) Sine wave Output AC waveform (AC mode) PWM sine wave Output AC waveform (AC mode) PWM sine wave INPUT Fated input current (at maximum load) Nominal Input Voltage(s) 120V AC Supported 10A UPS input connection type 5-15P Input circuit breaker 10A UPS Input cond length (th.) 6 UPS Input cord length (th.) 6 UPS Input cord length (th.) 6 BATTERY 15 A 120V BATTERY 10 minutes (150w) Half load runtime (minutes) 3.5 min. (300w) Half load runtime (minutes) 10 minutes (150w) LEDS ALARMS & SWITCHES LEDs indicate power status and overload/check battery status		300
Output voltage regulation (Battery mode) 115V (+/- 5%) Built-in UPS output receptacles 8 5-15R outlet(s) Surge suppression only outlets 4 UPS outlets, 4 surge-only outlets outlets Output AC waveform (AC mode) Sine wave Output AC waveform (Battery mode) PWM sine wave INPUT 10A Rated input current (at maximum load) 10A Nominal Input Voltage(s) Supported 120V AC UPS Input connection type 5-15P Input cornection type 5-15P Input cornection type 10A UPS Input cord length (ht) 6 UPS Input cord length (mt) 18. Recommended Electrical Service 15A 120V EATTERY 10 minutes (150w) Half load runtime (minutes) 10 minutes (150w) IDC system voltage (VDC) 12 LED Indicators 2 LEDs indicate power status and overload/check battery status	Nominal Output Voltage(s) Supported	115V; 120V
(Battery mode) Image: Comparison of the end of the en	Frequency compatibility	60 Hz
receptacles Surge suppression only outlets 4 UPS outlets, 4 surge-only outlets Output AC waveform (AC mode) Sine wave Output AC waveform (AC (battery mode) PWM sine wave INPUT PWM sine wave Rated input current (at maximum load) 10A Nominal Input Voltage(s) supported 120V AC UPS input connection type 5-15P Input circuit breaker 10A UPS Input cord length (ft.) 6 UPS Input cord length (ft.) 6 Recommended Electrical Service 15A 120V Full load runtime (minutes) 3.5 min. (300w) Haff load runtime (minutes) 12 DC system voltage (VDC) 12 LEDS ALARMS & SWITCHES 2LEDs indicate power status and overload/check battery status		115V (+/- 5%)
outiets Image: Constraint of the second		8 5-15R outlet(s)
mode) PWM sine wave Output AC waveform (battery mode) PWM sine wave INPUT Instant Composition (Composition (4 UPS outlets, 4 surge-only outlets
(battery mode) INPUT Rated input current (at maximum load) 10A Nominal Input Voltage(s) Supported UPS input connection type 5-15P Input circuit breaker 10A UPS Input cord length (ft.) 6 UPS Input cord length (m) 1.8 Recommended Electrical Service 15A 120V BATTERY Full load runtime (minutes) 3.5 min. (300w) Half load runtime (minutes) 0C system voltage (VDC) 12 LED Indicators 2 LEDs indicate power status and overload/check battery status		Sine wave
Rated input current (at maximum load) 10A Nominal Input Voltage(s) 120V AC Supported 120V AC UPS input connection type 5-15P Input circuit breaker 10A UPS Input cord length (ft.) 6 UPS Input cord length (m) 1.8 Recommended Electrical Service 15A 120V BATTERY 10 minutes (150w) Half load runtime (minutes) 3.5 min. (300w) Half load runtime (minutes) 12 LEDS ALARMS & SWITCHES 2 LEDs indicate power status and overload/check battery status	Output AC waveform (battery mode)	PWM sine wave
maximum load)120V ACNominal Input Voltage(s) Supported120V ACUPS input connection type5-15PInput circuit breaker10AUPS Input cord length (ft.)6UPS Input cord length (m)1.8Recommended Electrical Service15A 120VBATTERY	INPUT	
Supported UPS input connection type 5-15P Input circuit breaker 10A UPS Input cord length (ft.) 6 UPS Input cord length (m) 1.8 Recommended Electrical Service 15A 120V BATTERY 3.5 min. (300w) Half load runtime (minutes) 3.5 min. (300w) Half load runtime (minutes) 10 minutes (150w) DC system voltage (VDC) 12 LEDS ALARMS & SWITCHES 2 LEDs indicate power status and overload/check battery status		10A
Input circuit breaker 10A UPS Input cord length (ft.) 6 UPS Input cord length (m) 1.3 Recommended Electrical Service 15A 120V BATTERY 15A 120V Full load runtime (minutes) 3.5 min. (300w) Half load runtime (minutes) 10 minutes (150w) DC system voltage (VDC) 12 LEDS ALARMS & SWITCHES 2 LEDs indicate power status and overload/check battery status	Nominal Input Voltage(s) Supported	120V AC
UPS Input cord length (ft.) 6 UPS Input cord length (m) 1.8 Recommended Electrical Service 15A 120V BATTERY 15A 120V Full load runtime (minutes) 3.5 min. (300w) Half load runtime (minutes) 10 minutes (150w) DC system voltage (VDC) 12 LEDS ALARMS & SWITCHES 2 LEDs indicate power status and overload/check battery status	UPS input connection type	5-15P
UPS Input cord length (m) 1.8 Recommended Electrical Service 15A 120V BATTERY Image: Constraint of the service of the	Input circuit breaker	10A
Recommended Electrical Service 15A 120V BATTERY	UPS Input cord length (ft.)	6
Service BATTERY Full load runtime (minutes) 3.5 min. (300w) Half load runtime (minutes) 10 minutes (150w) DC system voltage (VDC) 12 LEDS ALARMS & SWITCHES 2 LEDs indicate power status and overload/check battery status	UPS Input cord length (m)	1.8
Full load runtime (minutes) 3.5 min. (300w) Half load runtime (minutes) 10 minutes (150w) DC system voltage (VDC) 12 LEDS ALARMS & SWITCHES 2 LEDs indicate power status and overload/check battery status		15A 120V
Half load runtime (minutes) 10 minutes (150w) DC system voltage (VDC) 12 LEDS ALARMS & SWITCHES 2 LEDs indicate power status and overload/check battery status	BATTERY	
(minutes) 12 DC system voltage (VDC) 12 LEDS ALARMS & SWITCHES 2 LEDs indicate power status and overload/check battery status	Full load runtime (minutes)	3.5 min. (300w)
LEDS ALARMS & SWITCHES LED Indicators 2 LEDs indicate power status and overload/check battery status		10 minutes (150w)
LED Indicators 2 LEDs indicate power status and overload/check battery status	DC system voltage (VDC)	12
	LEDS ALARMS & SWITCHES	3
Alarms Audible alarm indicates power-failure and overload status	LED Indicators	2 LEDs indicate power status and overload/check battery status
	Alarms	Audible alarm indicates power-failure and overload status
Switches Combination switch controls on/off power status and self-test operation	Switches	Combination switch controls on/off power status and self-test operation
	(minutes) DC system voltage (VDC) LEDS ALARMS & SWITCHES LED Indicators	12 2 LEDs indicate power status and overload/check battery status

SURGE / NOISE SUPPRESS	ION
UPS AC suppression joule rating	420
UPS AC suppression response time	Instantaneous
UPS Dataline suppression	1 line TEL/DSL (1 in / 1 out)
EMI / RFI AC noise suppression	Yes
PHYSICAL	
Installation form factors supported with included accessories	Tower; Ultra-compact desktop
Primary form factor	Desktop
UPS / Power Module dimensions in primary form factor (height x width x depth / inches)	3.1 x 5.7 x 10.8
UPS / Power Module dimensions in primary form factor (height x width x depth / cm)	7.8 x 14.6 x 27.6
UPS / Power Module weight (lbs)	6.5
UPS / Power Module weight (kg)	3
UPS Shipping dimensions (height x width x depth / inches)	4.1 x 8 x 13
UPS Shipping dimensions (height x width x depth / cm)	10.4 x 20.3 x 33
Shipping weight (lbs)	7
Shipping weight (kg)	3.2
UPS housing material	ABS
ENVIRONMENTAL	
Operating Temperature Range	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius
Storage Temperature Range	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius
Relative Humidity	0 to 95%, non-condensing
AC mode BTU / hr. (full load)	14
Battery mode BTU / hr. (full load)	194.3
COMMUNICATIONS	
Communications interface	USB (HID enabled)
PowerAlert software	Free download from www.tripplite.com

Communications cable	USB interface cable included
WatchDog compatibility	Supports Watchdog application, OS and hard-reboot restart options for remote applications
LINE / BATTERY TRANSFER	2
Transfer time	4 milliseconds (AC to battery mode) / 2 milliseconds (battery mode to AC)
Low voltage transfer to battery power (setpoint)	99
High voltage transfer to battery power (setpoint)	139
SPECIAL FEATURES	
Cold Start (startup in battery mode during a power failure)	Cold-start operation supported
Green & high efficiency features	Greater than 95% efficiency - GREEN UPS
CERTIFICATIONS	
UPS Certifications	Tested to UL1778 (USA); Tested to CSA (Canada); Tested to NOM (Mexico); Meets FCC Part 15 Category B (EMI); ENERGY STAR Qualified
WARRANTY	
Product Warranty Period (U.S. & Canada)	3-year limited warranty
Product Warranty Period (International)	2-year limited warranty
Product Warranty Period (Mexico)	3-year limited warranty
Product Warranty Period (Puerto Rico)	3-year limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$100,000 Ultimate Lifetime Insurance

Related Items

Optional Products

Related Model	Description	Qty.
CT120	Instant-Read- AC Outlet Circuit Tester	1
DCATV	Network Surge Suppressor - Essential protection for TV/VCR coaxial lines	1
DNET1	Network Surge Suppressor - Essential protection for data and communication lines	1
DTEL2	Network Surge Suppressor - Essential protection for data and communication lines	1
U005-10I	10-inch USB A/A Gold Extension Cable (USB-A Right Angle Male to USB-A Female)	1
U222-004-R	4-Port USB2.0 Ultra-Mini Hub	1
WATCHDOGSW	WatchDog Service Monitoring / Reboot Software	1
WEXT5-INTERNET	5-Year Extended Warranty - For Internet Office, AVR and ECO Series UPS Systems	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?variables.txtModelID=3063.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.