

LLA215R71E103MA14#

" # " indicates a package specification code.

Recommended



Reflow OK

Complies with RoHS

Low ESL

< List of part numbers with package codes >  
LLA215R71E103MA14L , LLA215R71E103MA14K

Shape



L size	2.0 ± 0.1mm
W size	1.25 ± 0.1mm
T size	0.5 +0.05/-0.1mm
Distance between external terminals P	0.5 ± 0.05mm
Size code in mm(inch)	2012 (0805)

References

Packaging	Specifications	Minimum quantity
L	180mm Embossed taping	4000
K	330mm Embossed taping	10000

Mass (typ.)	
1 piece	7.0mg
180mm Reel	140g

Specifications

Capacitance	10000pF ± 20%
Rated voltage	25Vdc
Temperature characteristics (complied standard)	X7R(EIA)
Capacitance change rate	± 15.0%
Temperature range of temperature characteristics	-55 to 125
Operating temperature range	-55 to 125

⚠ Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it ' s specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.