

LLL31MR70J475MA01#

" # " indicates a package specification code.

Recommended

Flow OK



Reflow OK

Complies with RoHS

Low ESL

< List of part numbers with package codes >
LLL31MR70J475MA01L , LLL31MR70J475MA01K

Shape



L size	1.6 ± 0.15mm
W size	3.2 ± 0.15mm
T size	1.15 ± 0.1mm
External terminal width e	0.35 ± 0.15mm
Distance between external terminals g	0.5mm min.
Size code in mm(inch)	1632 (0612)

References

Packaging	Specifications	Minimum quantity
L	180mm Embossed taping	3000
K	330mm Embossed taping	10000

Mass (typ.)	
1 piece	34mg
180mm Reel	149g


Specifications

Capacitance	4.7μF ± 20%
Rated voltage	6.3Vdc
Temperature characteristics (complied standard)	X7R(EIA)
Capacitance change rate	± 15.0%
Temperature range of temperature characteristics	-55 to 125
Operating temperature range	-55 to 125


⚠ Attention

- 1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it ’ s specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2.This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.


▪ Frequency characteristics (ESR, Impedance)




▪ S parameter (Smith chart S11)




▪ DC bias characteristics



▪ AC voltage characteristics



▪ Capacitance - temperature characteristics



▪ Calorific property by ripple current

