

## SMD Power Inductors (NR series)

## NR4010T4R7M



## ■ Features

- Item Summary  
4.7  $\mu$ H( $\pm 20\%$ ), 900mA, 750mA
- Lifecycle Stage  
Mass Production
- Standard packaging quantity (minimum)  
Taping 5000pcs

## ■ Products characteristics table


CaseSize (EIA/JIS)	~/4010
Inductance	4.7 $\mu$ H( $\pm 20\%$ )
Inductance Measuring Frequency	100kHz
Rated Current -Saturation Current	900mA
Rated Current -Temperature Rise Current	750mA
DC Resistance (max)	0.252 $\Omega$
Avg. of DC.Resistance	0.21 $\Omega$
Temperature Range	-25°C to 120°C
Self-resonant Frequency (min)	47MHz
RoHS Compliance	Yes
Halogen Free	Yes
Soldering Method	Reflow

## ■ External Dimensions

L	4mm $\pm 0.2$
W	4mm $\pm 0.2$
H	1mm max

## ■ Recommended Land Patterns

<b>【推奨ランドパターン】</b> 実装上の注意 ・実装状態を確認の上ご使用くださいようお願いいたします。 ・本製品のはんだ付けはリフローはんだ工法に限りま。
<b>【Recommended Land Patterns】</b> Surface Mounting ・Mounting and soldering conditions should be checked beforehand. ・Applicable soldering process to these products is reflow soldering only.



SMD Power Inductors (NR series/NR series H type/S type/V type)			
Type	A	B	C
NR 4010, NRS4010,			
NR 4012, NRS4012,	1.2	2.8	3.7
NR 4018, NRS4018			

unit:mm