

## SMD Power Inductors (NR series)

## NR6028T1R5N



## ■ Features

- Item Summary  
1.5  $\mu$ H ( $\pm 30\%$ ), 5000mA, 4200mA
- Lifecycle Stage  
Mass Production
- Standard packaging quantity (minimum)  
Taping 2000pcs

## ■ Products characteristics table

CaseSize (EIA/JIS)	~/6028
Inductance	1.5 $\mu$ H ( $\pm 30\%$ )
Inductance Measuring Frequency	100kHz
Rated Current -Saturation Current	5000mA
Rated Current -Temperature Rise Current	4200mA
DC Resistance (max)	0.0208 $\Omega$
Avg. of DC Resistance	0.016 $\Omega$
Temperature Range	-25°C to 120°C
Self-resonant Frequency (min)	78MHz
RoHS Compliance	Yes
Halogen Free	Yes
Soldering Method	Reflow

## ■ External Dimensions

L	6mm $\pm 0.2$
W	6mm $\pm 0.2$
H	2.8mm max

## ■ Recommended Land Patterns

【推奨ランドパターン】 実装上の注意 ・実装状態を確認の上ご使用くださいようお願いいたします。 ・本製品のはんだ付けはリフローはんだ工法に限りします。
【Recommended Land Patterns】 Surface Mounting ・Mounting and soldering conditions should be checked beforehand. ・Applicable soldering process to these products is reflow soldering only.



SMD Power Inductors (NR series/NR series H type/S type /V type)			
Type	A	B	C
NRS501.0, NR 601.2, NRS501.2, NRS501.4, NR 6020, NRS5020, NR 6028, NRS5028, NR 6045, NRS5045	1.6	4.7	5.7

unit: mm