

## SMD Power Inductors (NR series S type)

## NRS5020T220MMGJ



## ■ Features

- Item Summary  
22  $\mu$ H( $\pm 20\%$ ), 900mA, 1000mA
- Lifecycle Stage  
Mass Production
- Standard packaging quantity (minimum)  
Taping 800pcs

## ■ Products characteristics table


CaseSize (EIA/JIS)	~/5020
Inductance	22 $\mu$ H( $\pm 20\%$ )
Inductance Measuring Frequency	100kHz
Rated Current -Saturation Current	900mA
Rated Current -Temperature Rise Current	1000mA
DC Resistance (max)	0.312 $\Omega$
Avg. of DC.Resistance	0.26 $\Omega$
Temperature Range	-25°C to 125°C
Self-resonant Frequency (min)	17MHz
RoHS Compliance	Yes
Halogen Free	Yes
Soldering Method	Reflow

## ■ External Dimensions

L	4.9mm $\pm 0.2$
W	4.9mm $\pm 0.2$
H	2mm max

## ■ Recommended Land Patterns

【推奨ランドパターン】 実装上の注意 ・実装状態を確認の上ご使用ください。また、ご購入の際は、 本製品のほんたひは、リフローはんだ工法に準じます。
【Recommended Land Patterns】 Surface Mounting ・Mounting and soldering conditions should be checked beforehand. ・Applicable soldering process to these products is reflow soldering only.



SMD Power Inductors (NR series/NR series H type/S type /V type)			
Type	A	B	C
NRS010,			
NRS012,			
NRS014,			
NRS020,	1.5	3.6	4
NRS024,			
NRS030,			
NR 5040, NRS040			

unit:mm