

## SMD Power Inductors (NR series S type)

## NRS5020T4R7MMGJ



## ■ Features

- Item Summary  
4.7  $\mu\text{H}$ ( $\pm 20\%$ ), 2000mA, 2000mA
- Lifecycle Stage  
Mass Production
- Standard packaging quantity (minimum)  
Taping 800pcs

## ■ Products characteristics table

CaseSize (EIA/JIS)	~/5020
Inductance	4.7 $\mu\text{H}$ ( $\pm 20\%$ )
Inductance Measuring Frequency	100kHz
Rated Current -Saturation Current	2000mA
Rated Current -Temperature Rise Current	2000mA
DC Resistance (max)	0.072 $\Omega$
Avg. of DC.Resistance	0.06 $\Omega$
Temperature Range	-25°C to 125°C
Self-resonant Frequency (min)	37MHz
RoHS Compliance	Yes
Halogen Free	Yes
Soldering Method	Reflow

## ■ External Dimensions

L	4.9mm $\pm 0.2$
W	4.9mm $\pm 0.2$
H	2mm max

## ■ Recommended Land Patterns

【推奨ランドパターン】 実装上の注意 ・実装状態を確認の上ご使用ください。また、ご購入の際は、 本製品のほんたひはフローはんだ工法に準じます。
【Recommended Land Patterns】 Surface Mounting ・Mounting and soldering conditions should be checked beforehand. ・Applicable soldering process to these products is reflow soldering only.



SMD Power Inductors (NR series/NR series H type/S type /V type)			
Type	A	B	C
NRS010			
NRS012			
NRS014			
NRS020	1.5	3.6	4
NRS024			
NRS030			
NR 5040, NRS040			

unit:mm