


SMD Power Inductors (NS series)

NS10145T471MNA



■ Features

- Item Summary
470 μ H($\pm 20\%$), 0.61A, 0.52A
- Lifecycle Stage
Mass Production
- Standard packaging quantity (minimum)
Taping 2000pcs(500pcs*4reel)

■ Products characteristics table

CaseSize (EIA/JIS)	-/10145
Inductance	470 μ H($\pm 20\%$)
Inductance Measuring Frequency	100kHz
Rated Current -Saturation Current	0.61A
Rated Current -Temperature Rise Current	0.52A
DC Resistance (max)	1.236 Ω
Avg. of DC.Resistance	1.03 Ω
Temperature Range	-40°C to 125°C
Self-resonant Frequency (min)	2.8MHz
RoHS Compliance	Yes
Halogen Free	Yes
Soldering Method	Reflow


■ External Dimensions

L	10.1mm ± 0.3
W	10.1mm ± 0.3
H	4.5mm ± 0.35

■ Recommended Land Patterns

【推奨ランドパターン】
 実装上の注意
 ・実装状態を確認の上ご使用ください。また、お買い上げの際は、
 ・本製品のはんだ付けはリフローはんだ工法にのみ対応します。

【Recommended Land Patterns】
 Surface Mounting
 ・Mounting and soldering conditions should be checked beforehand.
 ・Applicable soldering process to these products is reflow soldering only.



SMD Power Inductors (NS series)			
Type	A	B	C
NS 10145	2.5	5.6	3.2
NS 10155	2.5	5.6	3.2
NS 10165	2.5	5.6	3.2
NS 12555	2.5	8.6	3.2
NS 12565	2.5	8.6	3.2
NS 12575	2.5	8.6	3.2

unit:mm