


SMD Power Inductors (NS series)

NS12555T680MN



■ Features

- Item Summary
68 μ H($\pm 20\%$), 1.81A, 2.14A
- Lifecycle Stage
Mass Production
- Standard packaging quantity (minimum)
Taping 2000pcs(500pcs*4reel)

■ Products characteristics table

CaseSize (EIA/JIS)	-/12555
Inductance	68 μ H($\pm 20\%$)
Inductance Measuring Frequency	100kHz
Rated Current -Saturation Current	1.81A
Rated Current -Temperature Rise Current	2.14A
DC Resistance (max)	0.09564 Ω
Avg. of DC.Resistance	0.0797 Ω
Temperature Range	-40°C to 125°C
Self-resonant Frequency (min)	7.9MHz
RoHS Compliance	Yes
Halogen Free	Yes
Soldering Method	Reflow


■ External Dimensions

L	12.5mm ± 0.3
W	12.5mm ± 0.3
H	5.5mm ± 0.35

■ Recommended Land Patterns

【推奨ランドパターン】
 実装上の注意
 ・実装状態を確認の上ご使用ください。また、ご購入の際は、本製品の仕様書を確認してください。
 ・本製品は、はんだ付けはリフローはんだ工法にのみ対応します。

【Recommended Land Patterns】
 Surface Mounting
 ・Mounting and soldering conditions should be checked beforehand.
 ・Applicable soldering process to these products is reflow soldering only.



SMD Power Inductors (NS series)			
Type	A	B	C
NS 10145	2.5	5.6	3.2
NS 10155	2.5	5.6	3.2
NS 10165	2.5	5.6	3.2
NS 12555	2.5	8.6	3.2
NS 12565	2.5	8.6	3.2
NS 12575	2.5	8.6	3.2

unit:mm