

# Low Voltage Lampholders



LH392



LH692

- ▶ Up to 50V
- ▶ MES or MBC bulb
- ▶ Flat and domed lens
- ▶ Brass or nylon bodies
- ▶ Red, Amber, Green, Blue and Clear lenses

**RoHS**

**RoHS compliant**

Bulbs will be supplied (dependant on order quantity) if a voltage is specified. These lampholders are suitable for up to 50V max.

Colors - Red, Amber, Green, (Clear & Blue, check availability).  
Brass bodies have polished chrome finish.

For Neon & Mains versions see page 75  
For Sealed version see page 84


**LH 692 7R**

SERIES CODE MODEL CODE VOLTAGE & COLOR  
see p 6

## ORDER FORMAT




### SERIES

**LH** Lampholder  
For  
T3 1/4 bayonet cap  
50V max




6.3 x 0.8

### MODEL

Code	Panel Hole Dia	Body Material	Dimension A	Max Panel Thickness	Terminal
<b>382</b>	19.0mm	Nylon	35.0mm	6.3mm	6.3 x 0.8
 Black nylon bezel with polycarbonate lens (Lens is L90 & Color)					
<b>392</b>	19.0mm	Nylon	35.0mm	6.3mm	6.3 x 0.8
 Chrome bezel with polycarbonate lens (Lens is L90 & Color)					
<b>692</b>	25.4mm	Brass	41.8mm	8.7mm	6.3 x 0.8
 Chrome bezel with polycarbonate lens (Lens is L117 & Color)					

### DIMENSIONS mm



### OPTIONS

#### Light sources

LEDs (6, 12, 24V)  
or  
Incandescent lamps are available

#### M445

P.V.C. Insulating terminal cover



#### Sealing

Neoprene washers to seal between bezel and panel (W23) and lens and bezel (W24) to give a seal equivalent to IP66 are available on most versions