



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: P940-19I

### 19-inch Serial ATA (SATA) Signal Cable (7Pin/7Pin)



#### Highlights

- Connect your high-speed Serial ATA device to a Serial ATA controller
- Support data transfer rates of up to 6.0 Gbps
- Cable is shielded to protect against EMI/RFI

#### Description

Tripp Lite expands its line of hard drive cables with the introduction of our new line of serial ATA cables. The signal cables connect any high speed Serial ATA device to a Serial ATA controller. Serial ATA delivers two significant benefits: it support much higher data transfer rates (up to 6.0 Gbps...backward compatible to 1.5Gbps) and the narrow cable design helps improve internal air flow. Perfect for the desktop or server that has multiple drives. These cables feature 7-pin straight/7-pin straight female connectors and offer easy installation.

#### System Requirements

- Serial ATA device
- Serial ATA controller

#### Package Includes



- 19-in. Serial ATA (SATA) Signal Cable 7Pin/7Pin, Straight/Straight

#### Features

- Connect your high-speed Serial ATA device to a Serial ATA controller
- Support data transfer rates of up to 6.0 Gbps
- Narrow cables design:
  1. simplifies cable routing and installation
  2. improves air flow within CPU (no more big ribbons blocking air movement)
- Meets Serial ATA 1.0 standards, including Errata 029
- Cable is shielded to protect against EMI/RFI

#### Specifications

OVERVIEW	
Intended Application	Connecting Peripherals
Cable Type	SATA
INPUT	

Cable Length (in.)	18
<b>UPC ASSIGNMENT</b>	
Unit Carton UPC#	037332118134
<b>PHYSICAL</b>	
Color	Red
Style	SATA
<b>CONNECTIONS</b>	
Connector A	 7 PIN SATA STRAIGHT (MALE)
Connector B	 7 PIN SATA STRAIGHT (MALE)
Number of Connectors	2
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	Lifetime limited warranty

## Related Items

### Optional Products

Related Model	Description	Qty.
<a href="#">P940-39I</a>	39-inch Serial ATA (SATA) Signal Cable (7Pin/7Pin)	1
<a href="#">P942-19I</a>	19-inch Serial ATA (SATA) Signal Cable (7Pin/7Pin-Down)	1
<a href="#">P944-06I</a>	6-inch Serial ATA (SATA) Power Cable (4Pin to 15pin)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=2646](http://www.tripplite.com/en/products/model.cfm?txtModelID=2646).

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.