



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: PDU6K

Power Distribution Unit (PDU) - Accessory adds additional outlet types to dual voltage UPS System

Highlights

- 8 outlet PDU system adds 240 and 120V output receptacles to select dual voltage 240/120V UPS systems
- Includes 4 ft. cord with L14-30 plug
- Input plug supports hardwire input connection
- Supports installation in 2U rackmount, wallmount and under-counter applications

Description

Tripp Lite's PDU6K AC power distribution unit offers 24 amp, 240/120V capacity in a versatile multi-mount cabinet. Detachable mounting flanges are configurable for wallmount, under-counter or 2U rackmount installation. Detachable flanges allow user configuration in dozens of potential mounting schemes. Includes 8 outlets total (1xL5-30R, 1xL5-20R, 2xL6-30R, 2xL6-20R, 1x6-20R), with NEMA L14-30P input plug. 4 ft. AC input cord.

PLUG/OUTLETS: Input: NEMA L14-30P/Output: 1 L5-30, 1 L5-20, 2 L6-30, 2 L6-20, 2 6-20R

ELECTRICAL: 240V AC input, 240/120V AC output

FORMAT: Supports 19 in. rackmount (2U), wallmount and under-counter

Applications

- Multi-outlet, dual voltage power distribution unit is the ideal means of adding additional types of plug in connections to the output of 240/120 dual voltage UPS systems.

Package Includes

- PDU6K rackmount power strip
- Instruction manual

Features

- Corded AC power distribution unit with 8 output receptacles
- Versatile all-metal cabinet with detachable mounting flanges allows wallmount, under-counter and 19 inch rackmount mounting in 2U format
- 4 120V and 4 240V output receptacles (1xL5-30R, 1xL5-20R, 2xL6-30R, 2xL6-20R, 1x6-20R)
- 4 ft. AC cord with L14-30 plug-in connection
- Removable plug enables hardwire input connection

Specifications

OUTPUT	
Circuit Breaker (amps)	20
Overload protection	20A resettable double pole breaker
Outlet quantity / type	8 outlets (120V: 1 L5-30R, 1 L5-20R, 2 Nema 6-20R / 240V: 2 L6-30R, 2 L6-20R)
INPUT	

Input connection type	Nema L14-30 input plug, removable for 4 wire hardwire installation
Input cord length (ft.)	4
Input cord length (m)	1.2
Voltage compatibility (VAC)	240
PHYSICAL	
Shipping Dimensions (HWD/in)	6.5 x 18.25 x 8.25
Shipping Dimensions (HWD/cm)	16.5 x 46.4 x 21
Shipping weight (lbs)	8
Shipping weight (kg)	3.6
Unit Dimensions (HWD/in)	3.5 x 17.25 x 3.75
Unit Dimensions (HWD/cm)	8.9 x 43.8 x 9.5
Unit weight (lbs)	6.25
Unit weight (kg)	2.8
Material of construction	Sheet metal
Mounting accessories included	Recessed rackmount installation brackets
Receptacle Color	Black
AC line cord color	Black
Form factors supported	2U rackmount, wallmount, under-counter
CERTIFICATIONS	
Approvals	UL1778 (USA), cUL (Canada), NOM (Mexico)

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=2653.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.