



DATE	SYM.	DESCRIPTION	DR	CK	REL




(4) EACH #10-32 BRASS INSERTS AND STAINLESS STEEL CAPTIVE COVER SCREWS WITH RETAINING O-RING



SECTION B-B

(4) EACH #10-32 BRASS INSERTS AND PLATED CARBON SCREWS

MATERIAL
BOX- COMPRESSION MOLDED FIBERGLASS REINFORCED POLYESTER
COVER- COMPRESSION MOLDED FIBERGLASS REINFORCED POLYESTER
WINDOWS- POLYCARBONATE



SECTION A-A

OPTIONAL BACK PANEL
0.100 [2.54] TH'K- ALUMINUM
0.075 [1.91] TH'K- WHITE STEEL-GALVANNEALED
0.125 [3.18] TH'K- FIBERGLASS


(4) STAINLESS STEEL MOUNTING FEET

(4) EACH #10-32 BRASS INSERTS, AND STAINLESS STEEL FEET SCREWS


(4) ϕ .34 [8.74]

FRONT VIEW
WITH COVER REMOVED
AND BACK PANEL SHOWN


BACK VIEW



30.5mm HOLE
DETAIL



DETAIL C
SCALE 1 : 1



PART No. PJ1206P16
for more information visit
www.hammfg.com
Data subject to change without notice
Drawing Not to Scale