PLASTICASE STYLE I



Ordering Information

Catalog Number	External Dimensions L x W x D
PC-11475	4.13" x 1.61" x 1.00"
PC-11476	5.12" x 3.00" x 1.18"
PC-11477	6.10" x 3.62" x 1.16"
PC-11478	7.87" x 4.76" x 1.57"

- Priced, sold and packaged in quantities of one
- Available June 10, 2009
- Contact the factory for other colors and/or modifications



BUD INDUSTRIES, INC. • 4605 E. 355th Street • Willoughby, Ohio 44094 • (440) 946-3200 • Fax (440) 951-4015 **E-MAIL:** saleseast@budind.com • **WEB SITE:** www.budind.com **BUD WEST** • 10000 N 31st Ave. Suite D-401 • Phoenix, Arizona 85051 • (602) 870-8377 • Fax (602) 870-8477

Trade name

• Plasticase – Style I

Benefits and Features

- Unique, contemporary styling with rounded corners and edges
- Durable, self-extinguishing, ABS plastic material with UL94-HB flammability rating
- Time saving 4 piece snap together design
- Internal PCB mounting bosses on lid & base
- Standard color: Light grey for base & lid. Grey for the end panels
- Textured surface on base & lid
- Textured surface on recessed area in end panels

Accessories

- Other colors are available upon request
- Modified versions available upon request
- Self-adhesive rubber feet

Applications

• Desktop or bench top electronic enclosure for a variety of applications

Competition and Competitive Advantages

- Pac-Tec
- Hammond
- OKW
- Bopla
- Lower cost
- In stock for same day delivery
- Easily modified by customer or by BUD
- Highest flammability rating available

Related Products

- Printed circuit boards
- Switches, LEDs, cables
- Keypads, LCDs,

Key Customer Contacts

- Design Engineers
- Manufacturing Engineers
- Purchasing Agents
- PCB Designers

Questions to Ask

- Who specifies your enclosures?
- Do you require a durable, electrically insulated enclosure?



BUD INDUSTRIES, INC. • 4605 E. 355th Street • Willoughby, Ohio 44094 • (440) 946-3200 • Fax (440) 951-4015 **E-MAIL:** saleseast@budind.com • **WEB SITE:** www.budind.com **BUD WEST** • 10000 N 31st Ave. Suite D-401 • Phoenix, Arizona 85051 • (602) 870-8377 • Fax (602) 870-8477