# RCE5C1H8R0D0M1H03A

"#" indicates a package specification code.





2.5 mm max.


5.0 +0.6/-0.2mm

 $0.5 \pm 0.05$ mm

6.0mm

< List of part numbers with package codes > RCE5C1H8R0D0M1H03A

## Shape



## Notes

Meet LF(lead Free), HF(Halogen Free)

#### References

Packaging	Specifications	Minimum quantity
A	Ammo pack taping type	2000

## Specifications

W1 size (max.)

Lead spacing F

Lead diameter d

T size

Capacitance	8.0pF ±5%
Rated voltage	50Vdc
Temperature characteristics (complied standard)	COG(EIA)
Capacitance change rate	± 0.5pF
Temperature coefficient	0 ± 30ppm/
Temperature range of temperature characteristics	25 to 125
Operating temperature range	-55 to 125

1 of 1

## **Attention**

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



muRata Murata Manufacturing Co., Ltd.

URL: http://www.murata.co.jp/

Last updated: 2013/12/07