

Model #: S118-000

SCSI/Fibre Channel - Passive External SCSI Terminator C50Male/Female Feed-Thru

Highlights

 Active terminators include a voltage regulator circuit to compensate for fluctuations in the host adapter



Description

Tripp Lite's feed-thru C50 passive terminator is the one for all of your external SCSI II applications. Used with SCSI devices which have a C50 female port. Tripp Lite's passive terminators provide the clearest data signal maximizing signal integrity. Supports fast and Ultra single ended devices at 10 or 20 Mbps. Passive terminators do not have a voltage regulator circuit to compensate for fluctuations in the host adapter. Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

System Requirements

• Any external use on a SCSI chain where a Cen50 Male terminator is required

Package Includes

• Passive External SCSI Terminator C50Male/Female Feed-Thru

Features

- Passive terminators do not have a voltage regulator circuit to compensate for fluctuations in the host adapter
- All Tripp Lite SCSI products, regardless of the SCSI generation, meet the latest specifications of ANSI
- Tripp Lite offers a complete line of internal and external solutions for SCSI/RAID and fibre channel ranging from the very latest Ultra 320 to legacy SCSI-1 and every combination in between
- Tripp Lite warrants this product to be free from defects in materials and workmanship for life

Specifications

UPC ASSIGNMENT	
Unit Carton UPC#	037332013866
PHYSICAL	
Style	Passive
CONNECTIONS	

Connector A	CENTRONICS 50 (MALE)
Connector B	CENTRONICS 50 (FEMALE)
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModeIID=2364.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.