



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: S366-006

6-ft. SCSI Double Shielded Cable (HD50 M/M)



Highlights

- Premium double-shielded cable
- 25 twisted-pair conductors

Description

Multi-platform SCSI II external peripheral cable HD50M/M. This 6ft cable is designed to connect two SCSI II (fast SCSI) devices together. Manufactured using double shielded 25 twisted pair high impedance cable. Constructed with low-capacitance, impedance matched, 28 AWG, stranded, tinned copper cable with insulated in polypropylene.

System Requirements

- Any external SCSI II device or controller card requiring HD50 interface

Package Includes

- 6Ft SCSI Cable HD50M to HD50M Double Shielded

Features

- Backwards compatibility with previous SCSI generations
- Double shielded (foil and braid)
- 25 twisted pair conductors
- All Tripp Lite SCSI products, regardless of the SCSI generation, meet the latest specifications of ANSI.
- Tripp Lite offers a complete line of internal and external solutions for SCSI/RAID and fibre channel ranging from the very latest Ultra 320 to legacy SCSI-1 and every combination in between

Specifications

OVERVIEW	
Intended Application	Connecting Drives
Cable Type	SCSI
Model Type	SCSI II External
INPUT	
Cable Length (ft.)	6

Cable Length (m)	1.83
UPC ASSIGNMENT	
Unit Carton UPC#	037332014078
PHYSICAL	
Color	Beige
Style	SCSI
CONNECTIONS	
Connector A	 HD50 (MALE)
Connector B	 HD50 (MALE)
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

Related Items

Optional Products

Related Model	Description	Qty.
S122-000	External Active SCSI Single-end Terminator (HD50 M)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.triplite.com/en/products/model.cfm?txtModelID=2389.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.