



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: S432-010

SCSI/Fibre Channel - 10-ft. SCSI Cable HD68M to centronic 50M Double Shielded

Highlights

- Premium double-shielded cable
- 34 twisted-pair conductors



Description

Multi-platform SCSI III to I external peripheral cable HD68M/C50M. This 10ft cable is designed to connect two SCSI III (fast and wide) or SCSI I devices together. Manufactured using double shielded 34 twisted pair high impedance cable. Constructed with low-capacitance, impedance matched, 28 AWG, stranded, tinned copper cable with insulated in polypropylene. Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

System Requirements

- Any external device or SCSI controller card requiring a HD68 or C50 interface

Package Includes



- 10-ft. SCSI Cable HD68M to Centronic 50M Double Shielded

Features

- Backwards compatibility with previous SCSI generations
- Double shielded (foil and braid)
- 34 twisted pair conductors
- All Tripp Lite SCSI products, regardless of the SCSI generation, meet the latest specifications of ANSI
- Tripp Lite offers a complete line of internal and external solutions for SCSI/RAID and fibre channel ranging from the very latest Ultra 320 to legacy SCSI-1 and every combination in between
- Tripp Lite warrants this product to be free from defects in materials and workmanship for life

Specifications

INPUT	
Cable Length (ft.)	10
UPC ASSIGNMENT	
Unit Carton UPC#	037332014191
CONNECTIONS	

Connector A	 HD68 (MALE)
Connector B	 CENTRONICS 50 (MALE)
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=2399.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.