

Model #: S455-006

6-ft. SCSI Ultra2/U160/U320 LVD Cable (VHDCI-M/HD68M)

Highlights

- Premium double-shielded cable
- Meets the most current SCSI specifications for high-speed devices



Description

Moving your network into the next phase of SCSI solutions? Look no further than Tripp Lite's brand of SCSI U320/U160 cables. Supports all legacy transfer rates including Ultra 320. Multi-platform SCSI III external peripheral cable, VHDCI68M/HD68M. This 6ft cable is designed to connect two SCSI III (fast and wide) or SCSI II devices together. Manufactured using double shielded 34 twisted pair high impedance cable. Constructed with low-capacitance, impedance matched, 28 AWG, stranded, tinned copper cable with insulated in polypropylene.

System Requirements

• Any external SCSI device or host controller card requiring VHDCI68 or HD68 interface

Package Includes

• 6-ft. SCSI U320/U160 LVD/SE cable, VHDCI68M to HD68M

Features

- Supports all SCSI transfer rates through 320Mbps
- LVD/SE compliant
- Backwards compatibility with previous SCSI generations
- Double shielded (foil and braid)
- 34 twisted pair conductors
- All Tripp Lite SCSI products, regardless of the SCSI generation, meet the latest specifications of ANSI
- Tripp Lite offers a complete line of internal and external solutions for SCSI/RAID and fibre channel ranging from the very latest Ultra 320 to legacy SCSI-1 and every combination in between

Specifications

OVERVIEW	
Intended Application	Connecting Drives
Cable Type	SCSI
Model Type	SCSI Ultra2/160/320 External

INPUT

Cable Length (ft.)	6		
Cable Length (m)	1.83		
UPC ASSIGNMENT			
Unit Carton UPC#	037332121332		
PHYSICAL			
Color	Black		
Style	SCSI		
CONNECTIONS			
Connector A	VHDCI68 (MALE)		
Connector B	• [
WARRANTY			
Product Warranty Period (Worldwide)	Lifetime limited warranty		

Related Items

Optional Products

Related Model	Description	Qty.
S140-000	External SCSI U320 LVD/SE Active Terminator (HD68 M)	1
S450-010	6-ft. SCSI Ultra2/U160/U320 LVD Cable (HD68 M/M w/thumbscrews)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModeIID=2803.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.