




## PANEL MOUNTING






▲  
BLACK  
METAL HOUSING



▲  
BLACK  
BUTTON

## NOTE:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
3. TERMINAL NUMBERS FOR REF ONLY
4. CIRCUIT: SPST OFF-MOMENTARY ON
5. CONTACT MATERIAL: Gold OVER SILVER
6. RATING: 500mA @ 48 VAC  
200mA @ 50 VDC  
200mA @250 VAC
7. ELECTRIC LIFE: 500,000 CYCLES AT FULL LOAD
8. CONTACT RESISTANCE: 50 MILLIOHM MAX. (INITIAL)
9. INSULATION RESISTANCE: 1,000 MEGA-OHM MIN. @ 500VDC.
10. DIELECTRIC STRENGTH: 1,500 VAC FOR 1 MINUTE.
- ▲11. OPERATING FORCE: 350 gf +/- 150 gf
12. OPERATING TEMPERATURE: -30°C TO +85°C.
13. CONTACT BOUNCE: 10ms MAX.
14. TRAVEL: 1.5±0.25MM
15. PANEL THICKNESS RANGE: 1.5 - 4.0 mm.
16. ▲DENOTES CRITICAL PARAMETER.
17. 2002/95/EC (ROHS) COMPLIANT
18. MAX TORQUE APPLIED TO MOUNTING NUT: 1.5Nm
19. HARDWARE INCLUDED:
  - 1) T081101 LOCK WASHER (QTY 1)
  - 2) T081102 HEX NUT (QTY 1)
  - 3) T081103 RUBBER O-RING (QTY 1)
20. SEAL RATING: IP65



E-SWITCH®

TITLE RP8400B2M1CEBLKBLKNIL

SCALE 2:1

DATE 5/12/2011

DR rc

DWG ST084006

REV A

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY  
TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

|     |        |                        |          |     |
|-----|--------|------------------------|----------|-----|
| A   | 19939  | RELEASE FOR PRODUCTION | 05/12/11 | BMA |
| REV | PCR NO | DESCRIPTION            | DATE     | BY  |