

New Version of LS03 (DL)

DESCRIPTION

Standard liquid Level Sensor.
The Sensor has to be mounted horizontally for best results.

FEATURES

Depending on mounting position / movement direction, the sensor opens or closes with the rising, respectively the sinking liquid level

Different versions available for mounting from outside


High Power switches available

APPLICATIONS


- Liquid container monitoring in
- Household
- Automotive
- Test & Measurement
- Control Technology

Request a Sample today!

Contact:
www.meder.com
Phone +49 7731 8399-0



• LS03 Mounting from outside!



COMMENTS DL-TYPE

- Mounting from outside
- Thread M16x2.0
- Insertion hole: Ø 22 – 24mm
- Suitable for low filling pressure
- Wall thickness max. 5mm
- PP and PA versions available

PA VERSION	
Stem, nut	Polyamide black
Float	Polyamide black
Seal	NBR
PP VERSION	
Stem, nut	Polypropylene white
Float	Polypropylene white
Seal	NBR

ORDER INFORMATION

Because of the special sealing, we need to create a BV number (customized part) .

- These BV numbers are already existing
- LS03/DL-PP-BV52154 (Contact 52, Cable 500W)
- LS03/DL-PA-BV85054 (Contact 85, Cable 500W)
- LS03/DL-PA-BV97054 (Contact 66, Cable 500W)
- LS03/DL-PP-BV97154 (Contact 66, Cable 500W)
- LS03/DL-PP-BV97315 (Contact 66, Cable 3000W)

Do you need another version? We will create them for you, with your required parameters!

New Version of LS03 (DK)

DESCRIPTION

Standard liquid Level Sensor.
The Sensor has to be mounted horizontally for best results.

FEATURES

Depending on mounting position / movement direction, the sensor opens or closes with the rising, respectively the sinking liquid level

Different versions available for mounting from outside


High Power switches available

APPLICATIONS


- Liquid container monitoring in Household
- Automotive
- Test & Measurement
- Control Technology

Request a Sample today!

Contact:
www.meder.com
Phone +49 7731 8399-0



- LS03 Mounting from outside!



COMMENTS DK TYPE

- Mounting from outside
- Thread M16x2.0
- Insertion hole: Ø 22 mm
- Suitable for high filling pressure
- Wall thickness min. 4mm
- PP and PA versions available

PA VERSION	
Stem, nut	Polyamide black
Float	Polyamide black
Seal	Viton
PP VERSION	
Stem, nut	Polypropylene white
Float	Polypropylene white
Seal	Viton

ORDER INFORMATION

Because of the special sealing, we need to create a BV number (customized part) .

- These BV numbers existing already
- LS03/DK-PA-BV96054 (Contact 66, Cable 500W)
- LS03/DK-PP-BV96154 (Contact 66, Cable 500W)
- LS03/DK-PP-BV96314 (Contact 66, Cable 3000W)

Do you need another version? We will create them for you, with your required parameters!

New Version of LS03 (GZ)

DESCRIPTION

Standard liquid Level Sensor. The Sensor has to be mounted horizontally for best results.

FEATURES

Depending on mounting position / movement direction, the sensor opens or closes with the rising, respectively the sinking liquid level

Different versions available for mounting from outside


High Power switches available

APPLICATIONS

- Liquid container monitoring in
- Household
- Automotive
- Test & Measurement
- Control Technology

Request a Sample today!

Contact:
www.meder.com
Phone +49 7731 8399-0



• LS03 Mounting from outside!

COMMENTS GZ-VERSION

- Mounting from outside
- Tapered 1/2" NPT Thread
- No sealing necessary
- Insertion hole: 1/2"
- PA Version available

ORDER INFORMATION

Because of the special design, we need to create a BV number (customized part) .

- These BV numbers are already existing
- LS03/GZ-PA-BV95054 (Contact 66, Cable 500W)
- LS03/GZ-PA-BV85154 (Contact 85, Cable 500W)

Do you need another version? We will create them for you, with your required parameters!

PA VERSION	
Stem	Polyamide black
Float	Polyamide black