



2.54 Typ.

RECOMMENDED P.C.B. LAYOUT



CIRCUIT: SPDT
CONTACT CONFIGURATION

SWITCH FUNCTION			
POS. 1	POS. 2	POS. 3	
			
DN	OFF	DN	
2-3	OPEN	2-1	

NOTES:

1. ALL DIMENSIONS IN MM
2. GENERAL TOLERANCE: $X.X = \pm 0.4$
 $X.XX = \pm 0.25$
3. TERM. NOS. FOR REF. ONLY
4. CONTACT RATING: 3A @120VAC OR 28VDC, 1A @250VAC
5. FIXED TERMINAL & MOVING CONTACT: Copper Alloy w/Silver Plate
6. ELECTRIC LIFE: 30,000 make-and-break cycles
at full load.
7. INSULATION RESISTANCE: 1,000 M ohm min.
8. DIELECTRIC STRENGTH: 1,000 V RMS @sea level.
9. OPERATING TEMP. -30°C to 85°C
10. DESIGNATE MAJOR DIMENSION



POS. 1, POS. 3

25.

E-SWITCH
MARKING ON
OPPOSITE SIDE

NO EPOXY ON TERMINALS
BELOW THIS SURFACE

—C—

E-SWITCH®

				E-SWITCH®			
				TITLE			
				200 MSP-3 T2 B1 M2 Q E			
SCALE		DATE		DR		DWG	
2:1		8/2/01		CJB		T212024	
						REV	
						A	