


Wirewound Power Radial Terminal Resistor

WPRT Series

- 10 to 50 watts
- Quick connect or soldered tag terminals
- Optional mounting bracket
- High overload capability
- AEC-Q200 qualified
- Flameproof case
- RoHS compliant




Electrical Data

		WPRT10	WPRT15	WPRT20	WPRT30	WPRT40	WPRT50
Power rating at 25°C	watts	10	15	20	30	40	50
Power rating at 70°C	watts	10	12.3	16.4	24.6	32.8	41
5s overload rating at 25°C	watts	50	75	100	150	200	250
Resistance range	ohms	1R0 - 820R	1R0 - 1K0	2R0 - 1K2	3R0 - 1K5	6R0 - 1K5	6R0 - 1K5
Thermal impedance	°C/watt	18	14	12	8.5	7	7
Isolation voltage	volts	1000					
TCR	ppm/°C	<20R: ±400, ≥20R: ±350					
Resistance Tolerance	%	±5					
Standard Values		E24					
Ambient temperature range	°C	-55 to +155					

Note: No LEV applies. Maximum voltage (dc or rms) is $\sqrt{P \times R}$

Physical Data

Figure 1 - soldered tag (S) and the same with bracket (SB)




Type	L ±1.5	W ±1.0	D ±1.0	P ±1.0	ØJ ±0.2	C ±0.4	ØB ±0.2	K ±1.0	F ±0.5	G ±0.5	E ±0.5	H ±1.0	Weight (nom.)	
													S	SB
WPRT10	48	10	9.0	32	4.1	5.5	2.5	3.0	8.7	5.0	12	18	11	16.5
WPRT15	48	12.5	11.5	32	4.1	6.2	2.5	3.0	8.0	6.0	12	21	18	24
WPRT20	63	12.5	13.5	44	4.1	6.2	2.5	3.0	10.0	6.0	12	21	27	34
WPRT30	75	19	19	54	4.1	7.6	3.2	4.0	9.5	7.5	18	32	66	80
WPRT40	90	19	19	70	4.1	7.6	3.2	4.0	9.5	7.5	18	32	81	94
WPRT50	90	19	19	70	4.1	7.6	3.2	4.0	9.5	7.5	18	32	81	94

General Note

TT electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT electronics' own data and is considered accurate at time of going to print.

Physical Data


Figure 2 - quick connect "amp" tag (A) and the same with bracket (AB)



All dimensions in mm and weights in g
Maximum bow on length and width <1.00mm

Type	L ±1.5	W ±1.0	D ±1.0	P ±1.0	ØJ ±0.2	K ±1.0	F ±0.5	G ±0.5	E ±0.5	H ±1.0	Weight (nom.)	
											A	AB
WPRT10	48	10	9.0	32	4.1	3.0	8.7	5.0	12	19	11	16.5
WPRT15	48	12.5	11.5	32	4.1	3.0	8.0	6.0	12	23.5	18	24
WPRT20	63	12.5	13.5	44	4.1	3.0	10.0	6.0	12	25	27	34
WPRT30	75	19	19	54	6.0	4.0	9.5	7.5	18	30	66	80
WPRT40	90	19	19	70	6.0	4.0	9.5	7.5	18	30	81	94
WPRT50	90	19	19	70	6.0	4.0	9.5	7.5	18	30	81	94

Figure 3 – as configuration A but with tighter tolerance terminal alignment (AT) and the same with bracket (AD)



All dimensions in mm and weights in g
Maximum bow on length and width <1.00mm


Type	L +0.5/-1.0	W +0.5/-1.0	D ±1.0	P ±0.3	ØJ ±0.2	K ±1.0	F ±0.5	G ±0.5	E ±0.5	H ±1.0	Weight (nom.)	
											AT	AD
WPRT10	48	10	9.0	32	4.1	3.0	8.7	5.0	12	19	11	16.5
WPRT15	48	12.5	11.5	32	4.1	3.0	8.0	6.0	12	23.5	18	24
WPRT20	63	12.5	13.5	44	4.1	3.0	10.0	6.0	12	25	27	34
WPRT30	75	19	19	54	6.0	4.0	9.5	7.5	18	30	66	80
WPRT40	90	19	19	68	6.0	4.0	9.5	7.5	18	30	81	94
WPRT50	90	19	19	68	6.0	4.0	9.5	7.5	18	30	81	94

General Note

TT electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT electronics' own data and is considered accurate at time of going to print.

Construction


A high purity ceramic rod, with force fit end caps onto which is wound a wire element. The element is fitted into a ceramic case with fireproof insulation cement. The terminal material is tin plated steel.

	Name	Main Material
	1 Rod	Al ₂ O ₃
	2 Filling Material	SiO ₂
	3 Ceramic Case	Al ₂ O ₃ CaO
	4 Terminal	Steel (tin plated)
	5 Bracket	Steel
	6 Wire Element	Resistance Alloy

- Termination Strength:** The terminations meet the requirements of IEC 86.2.21
- Marking:** Power rating, resistance value and tolerance are legend marked.
- Flammability:** The resistor will not burn under any condition of applied temperature or overload.
- Solvent resistance:** The body protection and marking are resistant to all normal industrial solvents suitable for printed circuits.

Performance Data


		Maximum
Load at rated power (1000hrs at 25°C and 70°C)	ΔR%	5
Derating from rated power		Zero at 275°C (see graph)
Short term overload (5 x rated power)	ΔR%	5 +0.05Ω
Damp heat steady state (56 days, 40°C, ≥90% RH)	ΔR%	5 +0.05Ω
Temperature rapid change (5 cycles -55°C to +155°C)	ΔR%	2 +0.05Ω
Resistance to solder heat	ΔR%	1 +0.05Ω
Voltage Proof (1kV for 60s)		No flashover, mechanical damage, arcing or breakdown
Solderability		Min. 95% coverage



General Note
TT electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT electronics' own data and is considered accurate at time of going to print.

Pulse Performance

The pulse energy capacity limits in the graph below relate to pulses below 100ms duration based on an instantaneous wire temperature rise of 750°C.



Application Notes

S and SB configurations have terminals which can be soldered. However, for full power operation, due to the possibility of high terminal temperatures, it is recommended that the connections be secured mechanically, rather than relying on the solder joint alone. AT and AD configurations are designed for use in molded housing assemblies, where the alignment of terminals and the body dimensions must be defined to a greater tolerance.

Ordering Procedure

Example: WPRT50 at 1.2 kilohms 5% tolerance with quick connect "amp" tag terminals and bracket, bulk packed in a box of 168 pieces –

Type WPRT50AB-1K2JB168

Power Rating _____

Configuration _____

S	Soldered tag without bracket	Figure 1
SB	Soldered tag with bracket	Figure 1
A	Quick connect "amp" tag without bracket	Figure 2
AB	Quick connect "amp" tag with bracket	Figure 2
AT	Configuration A with tighter tolerance terminal alignment	Figure 3
AD	Configuration AB with tighter tolerance terminal alignment	Figure 3

Value (use IEC62 code) _____

Tolerance (use IEC62 code) _____

Packing _____

B440	Bulk	WPRT10	440 / box	Standard
B400		WPRT15	400 / box	
B270		WPRT20	270 / box	
B240		WPRT30 / 40 / 50	S / A / AT	
B168			SB / AB / AD	

General Note

TT electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT electronics' own data and is considered accurate at time of going to print.