


REV S

FIG. 2


-MW: METAL WASHER
(ONE PER POSITION)
(5 POS. MIN, 30 POS. MAX)

UNLESS OTHERWISE NOTED				TITLE: ELEVATED 2MM C.L. ASM SOCKET	DWG NO: YTE-1XX-XX-XXX-X-XXX-XXX-XX SHEET 2 OF 2
DIMENSIONS ARE IN INCHES		TOLERANCES ARE:			
ONE PLACE DECIMALS ± .1[2.5]	THREE PLACE DECIMALS ± .005[.127]	TWO PLACE DECIMALS ± .01[.25]	FOUR PLACE DECIMALS ± .0020[.051]		
ANGLES ± 2°					


DO NOT SCALE
FROM THIS PRINT




-02 STYLE ONLY



IN PROCESS 1



IN PROCESS 2



IN PROCESS 3




FIG. 3

POLARIZATION OPTION LOCATION
INSERT PK-07 INTO SPECIFIED
POSITION AND BREAK OFF TAB

NOTE:

1. MINIMUM CONTACT
RETENTION: 0.5 LB PER PIN.

TABLE 1				
STYLE	ROW	NO. OF POS.	PKG TUBE	TUBE PLUG
-02	-Q	15-50	PT-1-24-03-51	TP-13
-03	-Q	15-50	PT-1-24-16-29	TP-07
-02, -03	-Q	02-14	LAYER PACKAGING	
-02	-5	15-50	PT-1-24-01-56	TP-31
-03	-5	15-50	PT-1-24-01-08	TP-13
-02, -03	-5	02-14	LAYER PACKAGING	
-02	-6	15-50	PT-1-24-02-74	TP-13
-03	-6	15-50	PT-1-24-01-08	TP-13
-02, -03	-6	02-14	LAYER PACKAGING	

PLOT SCALE: 1=.44 / DIMSCALE: .3

samtec

520 PARK EAST BLVD. NEW ALBANY, INDIANA 47150
PHONE (812) 944-6733 P.O. BOX 1147
CODE 55322

MADE BY:
BRATCHER 1-26-99

YTE-1XX-XX-XXX-X-XXX-XXX-XX
SHEET 2 OF 2

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION
CONFIDENTIAL AND PROPRIETARY TO
SAMTEC INC. AND SHALL NOT BE
REPRODUCED OR TRANSMITTED IN
ANY FORM OR BY ANY MEANS
ELECTRONIC OR MECHANICAL,
INCLUDING PHOTOCOPYING, RECORDING,
OR BY ANY INFORMATION STORAGE
AND RETRIEVAL SYSTEM, WITHOUT THE
WRITTEN CONSENT OF SAMTEC INC.