RJ45 MODULAR JACK WITH MAGNETIC FILTER

1 Port – SMT-Termination – Shielded





RoHS compliant - UL / cUL listed, File No.: E202784

PRODUCT DRAWING_

Description_

- According to specifications IEEE 802.3 and ANSI X3.263
- With and without LED
- Turns Ratio
 - 1:1 / 1:1 (Tx / Rx) or
 - 1:1.414/1:1 (Tx/Rx)
 - Further Turns Ratio on request
- Available with and without shunt choke option in transmission channel





11 4

gre

17.26

13.3 0.46 3.7±0.1

ORDER DATA_

0.88

RJ45 Magnetic modular Jack – 1 Port				
Design	Turns ratio	Shunt choke	LED	Part Number
SMT-Termination	1:1/1:1 (Tx/Rx)	In transmit channel	Without LED	RJ45SJS11ACONO X
SMT-Termination	1:1/1:1 (Tx/Rx)	In transmit channel	Green (left)/Yellow (right)	RJ45SJS11AC010 X
SMT-Termination	1:1/1:1 (Tx/Rx)	Without	Without LED	RJ45SJS11ANONO X
SMT-Termination	1:1/1:1 (Tx/Rx)	Without	Green (left)/Yellow (right)	RJ45SJS11AN010 X
SMT-Termination	1:1414/1:1 (Tx/Rx)	In transmit channel	Without LED	RJ45SJS11BCON0 X
SMT-Termination	1:1414/1:1 (Tx/Rx)	In transmit channel	Green (left)/Yellow (right)	RJ45SJS11BC010 X
SMT-Termination	1:1414/1:1 (Tx/Rx)	Without	Without LED	RJ45SJS11BNONO X
SMT-Termination	1:1414/1:1 (Tx/Rx)	Without	Green (left)/Yellow (right)	RJ45SJS11BN010 X