

MICRO SWITCH

FREEPORT ILLINOIS, U.S.A
A DIVISION OF HONEYWELL
FED. MFG. CODE 91020

SWITCH-BASIC

CATALOG LISTING
BM-2RQ1-A2

BM-2RQ1-A2

M

DRAWING
NUMBER

26

ISSUE

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

REPLACES

RELEASE NO. PR-3092

CHECK

07DEC07

ASD

CHECK

73

25-JAN-73

USD

CHECK

73

25-JAN-73

USD

CHECK

73

25-JAN-73

USD


CHECK

73

25-JAN-73

USD

CHECK



NOTES

- 1 MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF .139 MAX DIA ON 1.000 ± .002 CENTERS
- 2 HARDWARE FURNISHED UNASSEMBLED

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

CHARACTERISTICS

OPERATING FORCE-----9-13 OZ
RELEASE FORCE-----4 OZ MN
DIFFERENTIAL TRAVEL-----.0004-.0020
OVERTRAVEL-----.219 MIN

ELECTRICAL DATA

CONTACT ARRANGEMENT
S P D T
-L101- 22A-125, 250 OR 480 VAC
1/4HP-125 VAC; 1/2HP-250 VAC
1/2A-125 VDC; 1/4A-250 VDC
L288
L315
L318
22A 250V ~ T85 5E4

SCALE FULL

DO NOT SCALE PRINT
UNLESS OTHERWISE NOTED
DIMENSIONS ARE IN INCHES
TOLERANCES ARE
ONE PLACE (.01) ± .030
TWO PLACE (.001) ± .015
THREE PLACE (.0001) ± .005
ANGLES ±
WEIGHT .094 LB

RASTER

FO-52848

DRAWN