

CATALOG LISTING BZ-2R389-A2 PAGE 1 OF 1		MICRO SWITCH a Honeywell Division FED. MFG. CODE 91929		SWITCH - BASIC		CATALOG LISTING BZ-2R389-A2	
RASTER DRAWN	ISSUE B	REPLACES X115277-BZ	RELEASE NO. 0002700				
	REVISIONS A 0003616 AS FEB 04		CHECK 23 FEB 04				
	MDM		CHECK 18 DEC 03				
	MDM		CHECK 18 DEC 03				
	MDM		CHECK 18 DEC 03				
	MDM		CHECK 18 DEC 03				
	MDM		CHECK 18 DEC 03				
	MDM		CHECK 18 DEC 03				
	MDM		CHECK 18 DEC 03				
	MDM		CHECK 18 DEC 03				

NOTES

1 MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF $\phi .139$ MAX ON $1.000 \pm .002$ CENTERS

2 - TERMINAL IDENTIFICATION: C - COMMON, NC - NORMALLY CLOSED, NO - NORMALLY OPEN

ANSI Y14.5M-1982 APPLIES

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION

CHARACTERISTICS	ELECTRICAL DATA	SCALE FULL
OPERATING FORCE ----- 8 - 13 OZ	CONTACT ARRANGEMENT S P D T	DO NOT SCALE PRINT
DIFFERENTIAL FORCE ----- 1 1/2 - 3 1/2 OZ	L96	UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
DIFFERENTIAL TRAVEL ----- .0004-.0020	15A 125, 250 OR 480 VAC	ONE PLACE (.0) $\pm .030$
OVERTRAVEL ----- .005 MIN	1/8HP 125 VAC, 1/4HP 250 VAC	TWO PLACE (.00) $\pm .015$
	1/2A 125 VDC, 1/4A 250 VDC	THREE PLACE (.000) $\pm .005$
		ANGLES $\pm$
	L288 16A 250V $\sim$ T85 5E4	WEIGHT .063 LB