




(2,54 mm) .100"

IPL1 SERIES



IPL1-105-02-L-D-K

IPL1-120-01-L-D-RA-K

IPL1-110-02-L-S-K

SHROUDED POWER CABLE HEADER

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?IPL1

Insulator Material:

Natural LCP

Terminal Material:

Phosphor Bronze

Plating:

Sn or Au over 50µ" (1,27 µm) Ni

Operating Temp Range:

-55°C to +125°C

Voltage Rating:

675 VAC/954 VDC

RoHS Compliant:

Yes

Processing:

Lead-Free Solderable:

Yes

-S & -D (-02 Lead Style)

SMT Lead Coplanarity:

(0,10 mm) .004" max (02-05)

(0,13 mm) .005" max (06-10)

(0,15 mm) .006" max (11-25)

-SH SMT Lead Coplanarity:

(0,15 mm) .006" max (02-25)



Mates with:
MMSD, MMSS, IPD1
(Does not mate with IPS1)


Mates with discrete wire
cable assemblies
(IPD1 & MMSS Series)

Keyed
Polarization

Surface Mount,
Right Angle and
Vertical Through-hole

Align &
Latch™

CURRENT RATING (PER CONTACT)	
AMBIENT TEMP	MMSD/IPL1
20°C	7.4A
40°C	6.5A
60°C	5.9A
95°C	3.8A
6 POSITIONS (2x3) 20 AWG POWERED	



(2,54 mm)
.100" pitch



- Individually shrouded pins
- Align & Latch™ System

APPLICATION SPECIFIC OPTIONS

- With or without Plug Polarization.
 - Guide post holes
- Call Samtec.

IPL1 - 1 NO. PINS PER ROW - LEAD STYLE - PLATING OPTION - ROW OPTION - OPTION - K

02, 03, 04, 05, 06, 08,
10, 12, 15, 16, 20, 25
(Call Samtec for other sizes)

-01
= Through-hole

-02
= Surface Mount

-L
= 10µ" (0,25 µm)
Gold on contact,
Matte Tin on tail


-S
= Single Row Vertical

-SH
= Single Row Horizontal
(-02 lead style only)

-D
= Double Row Vertical

-RA
= Right Angle
(-01 lead style only)

-K
= Keyed Polarization



Note:
Other Gold plating options available.
Contact Samtec.

Note:
Some sizes, styles and options are non-standard, non-returnable.

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 SAMTEC NORTHWEST CALIFORNIA • Tel: 408-395-5900 SAMTEC SOUTHERN CALIFORNIA • Tel: 1-800-726-8329
SAMTEC AMERICA LATINA COMERCIO EXTERIOR LTDA • Tel: (+55 31) 3786 3227 SAMTEC UNITED KINGDOM • Tel: 44 01236 739292 SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0
SAMTEC FRANCE • Tel: 33 01 60 95 06 60 SAMTEC ITALY • Tel: 39 039 6890337 SAMTEC NORDIC/BALTIC • Tel: +46-84477280 SAMTEC BENELUX • Tel: 44 01236 739292
SAMTEC ISRAEL • Tel: 972-3-7526600 SAMTEC INDIA • Tel: +91-80-3272 1612 SAMTEC ASIA PACIFIC • Tel: 65 6745-5955 SAMTEC JAPAN • Tel: 045-475-1385 SAMTEC CHINA • Tel: 86-21-6083 3766
SAMTEC TAIWAN • Tel: 886-2-2735-6109 SAMTEC HONG KONG • Tel: 852-26904858 SAMTEC KOREA • Tel: 82-31-717-5685 SAMTEC ANZ • Tel: 613 9580 0683