


(2,00 mm) .0787" **LS2 SERIES**



SELF MATING HERMAPHRODITIC STRIP

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?LS2

Insulator Material: Black Liquid Crystal Polymer

Contact Material: Phosphor Bronze Plating: Au or Sn over

50μ" (1,27 μm) Ni Voltage Rating: 475 VAC mated with LS2 **Operating Temp Range:**

-55°C to +125°C Insertion Force: (Single contact only) 4 oz (1,11 N) avg. Withdrawal Force:

(Single contact only) 3 oz (0,83 N) avg. RoHS Compliant:

CURRENT RATING (PER CONTACT)	
AMBIENT TEMP	6 Contacts
20°C	5A
40°C	4.3A
60°C	3.6A
80°C	2.7A

Processing:


Lead-Free Solderable:

SMT Lead Coplanarity: (0,15 mm) .006" max

APPLICATION SPECIFIC OPTION

Alignment pin. Call Samtec.

Note: Some lengths, styles and options are non-standard, non-returnable.



Note: Other Gold plating

options available.

Contact Samtec.

(5,27)

208

(6,35) .250

(2,29)

= Right Angle

(Shroud

Up)

-RA1

-RA2

= Tape

& Reel

Packaging

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

Style -01

(0,50)

No. of positions x (2,00) .0787 + (1,57) .062

وولسسن

(2.00)

.0787

Style -02

(8,38)

(6,83)