

FED. MFG. CODE 91020

CATALOG LISTING
WZLN-2-RH3

CATALOG LISTING

CHARACTERISTICS	ELECTRICAL DATA
OPERATING FORCE ————— 3 LBS MAX	CONTACT ARRANGEMENT S P N C
RELEASE FORCE ————— 1/4 LB MIN	L96
PRETRAVEL ————— (3°) .078 MAX	15A 125, <u>250</u> OR 480 VAC
DIFFERENTIAL TRAVEL — (1/2°) .014 MAX	1/8 HP 125 VAC, 1/4 HP <u>250</u> VAC
OVERTRAVEL ————— (17°) .469 MIN	1/2A 125 VDC, 1/4A <u>250</u> VDC
	

TOLERANCES


APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR REFERENCE. UNLESS NOTED, TOLERANCES ARE ±

DIM. mm	TOL. mm/in	DIM. in	TOL. mm/in
NO PLACES	X	1/64	
ONE PLACE	X, X	0.4/018	X, X
TWO PLACES	X, X	0.16/008	X, X
THREE PLACES			X, X
ANGLES			X, XXX

DESIGN UNITS ☐ SIMETRIC

☒ US CUSTOMARY

THIRD ANGLE PROJECTION



WEIGHT . 850 LB PLUS LEADS